

# EPSON®

INK JET PRINTER

# STYLUS® PHOTO 785EPX

## Print precious moments with quality and ease

The EPSON Stylus Photo 785EPX offers up to 2880 x 720 dpi, quick-drying 6-color inks, BorderFree™ printing, plus photo printing with or without a computer from popular digital camera memory cards.

### Key Features

#### Convenient photo printing with or without a computer

- Supports popular digital camera memory cards such as CompactFlash™ Type I and II, SmartMedia™, IBM® Microdrive™, Secure Digital, and Memory Stick® with an adapter

#### True BorderFree photo printing

- Creates snapshots and enlargements quickly and easily without awkward perforations; works with 4" roll paper, and frame-ready 4" x 6", 5" x 7" or 8" x 10" borderless paper

#### Ultra fast print speeds

- Prints a 4" x 6" photo in 54 seconds and black text at up to 8 ppm\*

#### Superior, 6-color Photo Inks and 2880 x 720 dpi\*\* resolution

- Photo Quality with the widest array of colors for prints that look like traditional photographs
- Sharper detail, more accurate skin tones and vivid contrasts
- 4-picoliter ink droplets for smooth gradations

#### Built-in USB port

- Facilitates quick, easy setup with both Windows® and Macintosh® systems

#### PRINT Image Matching™ technology

- Automatically optimizes images captured by PRINT Image Matching-enabled digital cameras



PHOTO 785EPX



**EPSON**

INK JET PRINTER

**STYLUS PHOTO 785EPX****Specifications****Printing Method**

6-color (CcMmYK) Micro Piezo™ ink jet technology

**Resolution (dots per inch)\*\***

Up to 2880 x 720 dpi

**Print Speed\***

Black text memo	8 ppm
Photo	
4" x 6"	54 sec
8" x 10"	1 min 51 sec

**Printer Language**

EPSON ESC/P® Raster; EPSON Remote

**Software Drivers**

Windows USB – Windows 98, 2000, Me or later

Macintosh USB – Macintosh System 8.5.1 - 9.x

**Software**

EPSON Software™ Film Factory™ (PC/Mac)

Arcsoft™ PhotoImpression™ 3.0 (PC/Mac)

**Standard Interfaces**

USB

**Printable Area (using No Margin setting)**

8.5" x 11" (full-bleed letter size)

Top margin 0" Left margin 0"

Bottom margin 0" Right margin 0"

Maximum paper size up to 8.5" x 44"

**PCMCIA Type II card slot**

PCMCIA Type I adapter included (supports CompactFlash Type I memory card)

PCMCIA adapter for Memory Stick, Secure Digital, SmartMedia,

CompactFlash Type II and IBM Microdrive sold separately.

Supports Digital Print Order Format (DPOF)

**Paper Capacity**

Input paper tray 100 sheets/10 envelopes/1 transparency

Output paper tray 30 sheets

**Physical Characteristics (L x W x H)**

18.4" x 10.1" x 8.4"/11.6 lb

**Ink Cartridge Life**Black ink life 540 pages text (ISO/IEC 10561 letter pattern);  
378 pages graphic (5% coverage)

Color ink life 220 pages (15% coverage)

Shelf life 2 years from production date;  
6 months from first cartridge use**Optional Preview Monitor**

1.6" color preview monitor for easy review and selection of your images.

**Warranty**

Standard one year limited warranty including EPSON Exchange program (U.S. and Canada only)

\* Black text is in Economy Mode on plain paper. Color photo is in Fine Mode on EPSON Photo Paper. Additional processing time will vary based on system configuration, software application, and page complexity.

\*\* On EPSON Photo Paper, EPSON Premium photo papers and EPSON Photo Quality Glossy Film.

**EPSON**[www.epson.com](http://www.epson.com)

**Epson America, Inc.**  
3840 Kilroy Airport Way  
Long Beach, CA 90806

**Epson Canada, Ltd.**  
550 McNicoll  
Willowdale, Ontario M2H 2E1

**Epson Latin America, Inc.**  
6303 Blue Lagoon Drive  
Miami, FL 33126

Specifications and terms are subject to change without notice. EPSON and EPSON Stylus are registered trademarks and Micro Piezo and PRINT Image Matching are trademarks of Seiko Epson Corporation. BorderFree is a trademark and Epson Connection is a service mark of Epson America, Inc. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks.  
© Copyright 2001 for Epson America, Inc. CPD-11545 50K 5/01 CL